

Flush Clip Installation Instructions

Please provide these instructions to contractor at point of sale.

This fitting is designed to allow the glass to contact the back wall. It is intended to be used with $1\frac{1}{16}$ " to $1\frac{3}{16}$ " (17-21) thick laminated glass to support the back of the Counter only. It should be attached to the wall using a flat-headed, #14 screw appropriate for the surface on which it is used. We recommend the use of blocking or an adequate anchoring device inside the wall for a strong installation.

This mount offers little strength without the aid of additional support on an opposing side such as a Vitraform Console Leg, Vitraform Two Part Support Leg, Vitraform Side Wall Support or Surface Clips.

The **Flush Clip** is not adjustable or "levelable" so it is essential to locate and drill mounting holes accurately. When planning this installation remember that the glass is NOTCHED where the **Flush Clip** is to be installed, allowing only minor horizontal tolerance, so care must be taken that it is located correctly.

The glass Counter is held in position to the **Flush Clip** by tightening a $\frac{1}{2}$ " **Nylon Set Screw** using a $\frac{1}{4}$ " Allen wrench. This set screw is designed to provide enough pressure to hold the glass from sliding yet allow some cushion for expansion and contraction of the glass and clip. When tightening the set screw make sure the Allen wrench is completely inserted into the hexagonal socket in the set screw to avoid stripping the socket.

SECTION

